

AMP Terrain Attack A/T

With an off-road attitude and smooth on-road characteristics, the AMP Terrain Attack A/T A is the ultimate adventure tire. The performance tread design features a multi-block pattern that delivers stable control in a wide variety of environments and terrain. Equipped with a large selection of sizing and a 40,000 mile warranty, let the Terrain Attack take you on every journey.

PERFORMANCE TREAD DESIGN

Unique multi-block tread design ensures smooth ride quality along with superior off road handling and grip.

TWIN LUG SIDEWALL

Sidewall designed with dual variation lug technology for greatly improved traction in all environments and weather conditions.

OFF ROAD PERFORMANCE

The staggered tread block design was made to improve traction in loose dirt, debris and sand.

TREAD DEPTH

Deep, stepped tread blocks channel dirt, mud, and water away from the tire in all weather conditions.

Part No.	Size	Diameter	Speed	Load Range	Weight	Tread Depth	Overall Diameter	Overall Width	Max. Load	Max. Press.	Tread Construction	Approved Rim Width Range
17"												
265-7017AMP/CA3	LT265/70R17	17	121/118S	E	53.8	15.5	31.7	10.7	3195LBS/2910LBS	80PSI	2P+2S+1N	7.0-9.0
285-7017AMP/CA3	LT285/70R17	17	121/118R	E	56.5	15.5	32.8	11.5	3195LBS/2910LBS	80PSI	2P+2S+1N	7.5-9.5
315-7017AMP/CA3	LT315/70R17	17	121/118R	E	62.4	15.5	34.4	12.7	3195LBS/2910LBS	65PSI	2P+2S+1N	8.0-10.5
18"												
305-6018AMP/CA3	LT305/60R18	18	121/118R	E	58.9	15.5	32.4	12.2	3195LBS/2910LBS	65PSI	2P+2S+1N	9.0-11.0
305-7018AMP/CA3	LT305/70R18	18	126/123R	E	63.1	15.5	34.8	12.2	3750LBS/3415LBS	65PSI	2P+2S+1N	8.0-10.0
20"												
265-5020AMP/CA3	LT265/50R20	20	115/112S	E	51.7	15.5	30.5	10.9	2680LBS/2470LBS	80PSI	2P+2S+1N	8.0-9.5
275-5520AMP/CA3	LT275/55R20	20	115/112S	D	53.9	15.5	31.9	11.2	2680LBS/2470LBS	65PSI	2P+2S+1N	8.0-9.5
285-5520AMP/CA3	LT285/55R20	20	122/119S	E	58.4	15.5	32.4	11.7	3305LBS/3000LBS	80PSI	2P+2S+1N	8.0-10.0
305-5520AMP/CA3	LT305/55R20	20	121/118S	E	63.3	15.5	33.2	12.4	3195LBS/2910LBS	65PSI	2P+2S+1N	9.0-11.0
35-125020AMP/CA3	35×12.50R20LT	20	121R	E	66.9	15.5	34.5	12.5	3195LBS	65PSI	2P+2S+1N	8.5-11.0
37-125020AMP/CA3	37×12.50R20LT	20	126R	E	69.5	15.5	36.5	12.5	3750LBS	65PSI	2P+2S+1N	8.5-11.0
22"												
305-4022AMP/CA3	305/40R22	22	114S	XL	48.4	13.9	31.6	12.3	2601LBS	50PSI	2P+2S+1N	10.0-12.0
33-125022AMP/CA3	33×12.50R22LT	22	109R	E	60.3	15.5	32.5	12.5	2270LBS	65PSI	2P+2S+1N	8.5-11.0
35-125022AMP/CA3	35×12.50R22LT	22	117R	E	64.0	15.5	34.5	12.5	2835LBS	65PSI	2P+2S+1N	8.5-11.0