

AMP Terrain Attack R/T

Designed for the true off-road enthusiast, the all-new Amp Terrain Attack R/T is engineered to conquer the toughest terrains with ease, delivering exceptional performance and durability, without compromising on-road comfort. Featuring an innovative tread design that optimizes road contact & reduces road noise, the Terrain Attack R/T will conquer any terrain.

2 SIDEWALL DESIGNS. SAME OPTIMAL PERFORMANCE.

Designed for the true off-road enthusiast, the all-new Amp Terrain Attack R/T is engineered to conquer the toughest terrains with ease, delivering exceptional performance and durability, without compromising on-road comfort. Featuring an innovative tread design that optimizes road contact & reduces road noise, the Terrain Attack R/T will conquer any terrain.

OFF-ROAD TRACTION

Stone ejectors channel away water, mud, rocks, & other debris to maintain maximum grip & performance.

ALL-SEASON PERFORMANCE

Large, open shoulder blocks greatly improve off-road traction & enhance grip in extreme weather conditions.

LONG-LASTING DURABILITY

Staggered sidewall provides protection against punctures & abrasions in harsh environments.

Part No.	Size	Diameter	Speed	Load Range	Tread Depth	Overall Diameter	Overall Width	Max. Load	Max. Press.	Tread Construction	Approved Rim Width Range
17"											
285-7017AMP/RTC	LT285/70R17	17	116/113Q	C	16.4	32.8	11.5	2755/2535LBS	50PSI	2P+2S+1N	7.5-9.5 (8.5)
265-7017AMP/RTSL	P265/70R17	17	113T	SL	14	31.7	10.7	2535LBS	44PSI	2P+2S+1N	7.0-9.0 (8.0)
35-125017AMP/RTE	35X12.50R17LT	17	125Q	E	18.9	34.8	12.5	3640LBS	65PSI	2P+2S+1N	8.0-10.5 (10.0)
20"											
285-5520AMP/RTE	LT285/55R20	20	122/119Q	E	16.4	32.6	11.7	3305/3000LBS	80PSI	2P+2S+1N	8.5-10.0 (9.0)
35-125020AMP/RTF	35X12.50R20LT	20	125Q	F	18.9	34.8	12.5	3640LBS	80PSI	3P+2S+2N	8.5-11.0 (10.0)
35-125020AMP/RTE	35X12.50R20LT	20	121Q	E	18.9	34.8	12.5	3195LBS	65PSI	2P+2S+1N	8.5-11.0 (10.0)
33-125020AMP/RTE	33X12.50R20LT	20	114Q	E	18.9	32.8	12.5	2600LBS	65PSI	2P+2S+1N	8.5-11.0 (10.0)
305-5520AMP/RTF	LT305/55R20	20	125/122Q	F	16.4	33.5	12.4	3640/3305BS	80PSI	3P+2S+2N	9.0-11.0 (9.5)
22"											
35-125022AMP/RTF	35X12.50R22LT	22	121Q	F	18.9	34.8	12.5	3195LBS	80PSI	3P+2S+2N	8.5-11.0 (10.0)
35-125022AMP/RTE	35X12.50R22LT	22	117Q	E	18.9	34.8	12.5	2835LBS	65PSI	2P+2S+1N	8.5-11.0 (10.0)
33-125022AMP/RTF	33X12.50R22LT	22	114Q	F	18.9	32.8	12.5	2600LBS	80PSI	3P+2S+2N	8.5-11.0 (10.0)
33-125022AMP/RTE	33X12.50R22LT	22	109Q	E	18.9	32.8	12.5	2270LBS	65PSI	2P+2S+1N	8.5-11.0 (10.0)
24"											
35-135024AMP/RTF	35X13.50R24LT	24	116Q	F	18.9	34.8	13.4	2755LBS	80PSI	3P+2S+2N	11.5-13.5 (12.0)
35-135024AMP/RTE	35X13.50R24LT	24	112Q	E	18.9	34.8	13.4	2470LBS	65PSI	2P+2S+2N	11.5-13.5 (12.0)
37-135024AMP/RTF	37X13.50R24LT	24	124Q	F	18.9	36.8	13.6	3525LBS	80PSI	3P+2S+2N	9.5-12.0 (11.0)
37-135024AMP/RTE	37X13.50R24LT	24	120Q	E	18.9	36.8	13.6	3085LBS	65PSI	2P+2S+1N	9.5-12.0 (11.0)