

AMP Terrain Pro A/T

The AMP Terrain Pro A/T delivers a longer tread life and withstands demanding environments. With deep, multi-function tread grooves it provides enhanced traction in a wide variety of conditions while delivering a smooth and controlled ride. A broad selection of sizing and a 60,000 mile warranty drive the Terrain Pro A/T to be the leader of the pack.

OFF ROAD PERFORMANCE

Advanced compound prevents chipping and delivers a longer tread life with more consistent contact surface to deliver a smooth and controlled ride.

PERFORMANCE TREAD DESIGN

Stepped tread blocks allow more stable control and multi-direction sipes create greater traction.

TWIN LUG SIDEWALL

Unique “twin peaks” sidewall and open shoulder design delivers assertive performance in every condition and help evacuate water & mud for improved traction.

TREAD DEPTH

Deep grooves and rock ejectors keep tread grooves free of mud, dirt and gravel while mitigating possible punctures.

Part No.	Size	Diameter	Speed	Load Range	Weight	Tread Depth	Overall Diameter	Overall Width	Max. Load	Max. Press.	Tread Construction	Approved Rim Width Range
17"												
265-7017AMP/CA2	LT265/70R17	17	121/118S	E	47.7	15.1	31.7	10.7	3195LBS/2910LBS	80 PSI	2P+2S+1N	7.0-9.0
285-7017AMP/CA2	LT285/70R17	17	121/118R	E	54.6	15.1	32.8	11.5	3195LBS/2910LBS	80 PSI	2P+2S+1N	7.5-9.5
315-7017AMP/CA2	LT315/70R17	17	121/118R	E	65.2	15.1	34.4	12.7	3195LBS/2910LBS	65 PSI	2P+2S+1N	8.0-10.5
18"												
275-7018AMP/CA2	LT275/70R18	18	125/122R	E	60.1	15.8	33.2	11.0	3640LBS/3305LBS	80PSI	2P+2S+1N	7.0-9.0
285-6518AMP/CA2	LT285/65R18	18	125/122R	E	56.2	15.8	32.6	11.5	3640LBS/3305LBS	80 PSI	2P+2S+1N	8.5-10.0
325-6518AMP/CA2	LT325/65R18	18	127/124R	E	64.1	15.8	34.6	13.0	3860LBS/3525 LBS	65 PSI	2P+2S+1N	9.5-11.5
20"												
265-6020AMP/CA2	LT265/60R20	20	121/118S	E	51.5	15.1	32.5	10.7	3195LBS/2910LBS	80 PSI	2P+2S+1N	8.0-9.5
275-5520AMP/CA2	LT275/55R20	20	115/112S	D	55.2	15.8	31.9	11.2	2680LBS/2470LBS	65PSI	2P+2S+1N	8.0-9.5
275-6020AMP/CA2	LT275/60R20	20	123/120S	E	56.0	15.8	33.0	11.0	3415LBS /3085LBS	80 PSI	2P+2S+1N	8.0-9.5
275-6520AMP/CA2	LT275/65R20	20	126/123S	E	55.0	15.1	34.1	11.0	3750LBS /3415LBS	80 PSI	2P+2S+1N	8.0-9.5
285-5520AMP/CA2	LT285/55R20	20	122/119S	E	55.8	15.8	32.4	11.7	3305LBS/3000LBS	80 PSI	2P+2S+1N	8.5-10.0
285-6020AMP/CA2	LT285/60R20	20	125/122S	E	55.3	15.1	33.5	11.5	3640LBS/3305LBS	80 PSI	2P+2S+1N	8.5-10.0
295-6520AMP/CA2	LT295/65R20	20	129/126R	E	66.7	15.5	35.1	11.8	4080LBS/3750LBS	80PSI	2P+2S+1N	8.5-10.5
305-5520AMP/CA2	LT305/55R20	20	121/118S	E	62.2	15.8	33.2	12.4	3195LBS/2910LBS	65 PSI	2P+2S+1N	9.0-11.0
33-125020AMP/CA2	33X12.50R20LT	20	114S	E	61.7	15.8	32.5	12.5	2600LBS	65PSI	2P+2S+1N	8.5-11.0
35-125020AMP/CA2	35X12.50R20LT	20	121S	E	66.0	15.5	34.5	12.5	3195LBS	65PSI	2P+2S+1N	8.5-11.0
325-6020AMP/CA2	LT325/60R20	20	126/123S	E	68.1	15.8	35.4	13.0	3750LBS /3415LBS	65 PSI	2P+2S+1N	9.5-11.5
22"												
285-4522AMP/CA2	LT285/45R22	22	117R	D	52.8	15.8	32.1	11.2	2835LBS	65PSI	2P+2S+1N	9.0-10.5
285-5522AMP/CA2	LT285/55R22	22	124/121R	E	60.7	15.5	34.4	11.7	3525LBS/3195LBS	80PSI	2P+2S+1N	8.5-10.0
295-5022AMP/CA2	LT295/50R22	22	122/119S	E	63.4	15.8	33.7	12.2	3305LBS/3000LBS	80PSI	2P+2S+1N	8.5-10.5
24"												
305-3524AMP/CA2	P305/35R24	24	112S	XL	49.2	14.4	32.5	12.2	2469LBS	50PSI	2P+2S+1N	10.0-12.0
33-125024AMP/CA2F	33x12.50R24LT	24	106R	F	56.2	15.8	32.5	12.6	2095LBS	80PSI	2P+2S+1N	10.5-12.5
35-125024AMP/CA2F	35X12.50R24LT	24	116R	F	62.7	15.8	34.5	12.5	2755LBS	80PSI	2P+2S+1N	10.0-12.0