

BFGOODRICH®

ALL-TERRAIN T/A® KO2

Our toughest all-terrain tire. Ever. Now backed by a 50,000-Mile Warranty and 60-Day Satisfaction Guarantee⁴.

**BENEFITS OF BFGOODRICH® TIRES****20% Tougher Sidewalls¹.**

CoreGard™ Technology: Derived from the race-proven BFGoodrich® Baja T/A® KR2 tire.

1. Split- and bruise-resistant sidewall rubber.
2. Increased rubber thickness.
3. Advanced Deflection Design prevents protruding objects from snagging and splitting the sidewall.

50,000-mile manufacturer's treadwear limited warranty across all replacement sizes².

1. Locking 3-D Sipes provide increased tread block stability for more even wear over the long haul.
2. Advanced tire footprint shape more evenly distributes stress for longer, more uniform wear.

Aggressive all-terrain traction to confidently go where you want to go³.

1. Serrated shoulder design provides increased mud, snow and rock traction, especially in aired-down driving conditions.
2. Interlocking tread elements maximize traction and handling on- and off-road by stabilizing the tread center and providing biting edges for improved traction.
3. Three-peak mountain snowflake symbol: Exceeds U.S. Tire Manufacturers Association (USTMA) Severe Snow Traction performance requirements.

60-Day Satisfaction Guarantee⁴.

We're confident you'll love your new BFGoodrich® All-Terrain T/A® KO2 replacement tires. So confident, in fact, that we back your purchase with a 60-Day Satisfaction Guarantee. If you're not 100% satisfied with your new tires, just bring the tires and original sales receipt back to the place where you bought the tires within 60 days of your purchase and we will gladly exchange them for a new set of tires of equal or lesser value.

**60-DAY
SATISFACTION
GUARANTEE**

WEAR LIFE 9

FUEL EFFICIENCY 6

OFF-ROAD 8

BRAKING 7

COMFORT 7

**ORIGINAL
EQUIPMENT FITMENTS:**

Ford F-150 Raptor
Ford Bronco
Jeep Wrangler JK
Jeep Wrangler JL

¹Improvement depends on the size of the tire purchased, 20% improvement based on internal sidewall splitting test results derived from a simulated sidewall aggression testing machine (patent pending US20120245859A1) vs. the BFGoodrich® All-Terrain T/A® KO tire in size LT265/70R17. Actual on-road results may vary.

²Excludes Original Equipment tires.

³Snow: Based on third-party snow traction tests vs. the BFGoodrich® All-Terrain T/A® KO tire in size LT 265/70R17 using the ASTM F1805 Test. Mud Traction: Based on internal subjective mud testing vs. the BFGoodrich® All-Terrain T/A® KO tire in size LT 265/70R17.

⁴Guarantee applies to up to 6 tires per customer. Guarantee applies only to tires that were purchased and mounted and does not apply to exchanged tires that were provided under this guarantee. The guarantee does not include the cost of valve stems. Tires that are damaged due to misuse or misapplication, road hazards, mechanical problems related to the vehicle, use in any racing-related activities, or competitive events or tires that are removed from the original vehicle on which they were installed are excluded from guarantee.

BFGOODRICH® ALL-TERRAIN T/A® KO2

Tire Size	Service Description	Other	Limited Warranty	Side-wall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width (inches)	Overall Diameter (inches)	Tread Depth (in/32nds)	Rev/ Mile @45 mph	Max Load Single (lbs@psi)	UTQG	OE FITMENTS
30x9.50R15/C	104S	M + S, 3PMSF	50K	RWL	64055	6.5 - 8.5	9.5 on 7.5	29.5	15	705	1990@50		
31x10.50R15/C	109S	M + S, 3PMSF	50K	RWL	69948	7 - 9	10.5 on 8.5	30.5	15	682	2270@50		
32x11.50R15/C	113R	M + S, 3PMSF	50K	RWL	13079	8 - 10	11.5 on 9	31.5	15	659	2535@50		
33x10.50R15/C	114R	M + S, 3PMSF	50K	RWL	11548	7 - 9	10.5 on 8.5	32.5	15	640	2600@50		
33x12.50R15/C	108R	M + S, 3PMSF	50K	RWL	37881	8.5 - 11	12.5 on 10	32.5	15	640	2205@35		
35x12.50R15/C	113Q	M + S, 3PMSF	50K	RWL	33572	8.5 - 11	12.5 on 10	34.5	15	602	2535@35		
33x12.50R17/E	120S	M + S, 3PMSF	50K	RBL	36394	8.5 - 11	12.5 on 10	32.5	15	640	3085@65		
34x10.50R17/D	120R	M + S, 3PMSF	50K	RWL	91644	7 - 9	10.5 on 8.5	33.5	15	621	3085@65		
35x12.50R17/E	121R	M + S, 3PMSF	50K	RWL	66539	8.5 - 11	12.5 on 10	34.5	15	602	3195@65		
37x12.50R17/C	116S	M + S, 3PMSF	50K	RBL	80088	8.5 - 11	12.5 on 10	36.5	15	569	2755@45		FOR
37x12.50R17/D	124R	M + S, 3PMSF	50K	RWL	35666	8.5 - 11	12.5 on 10	36.5	15	569	3525@50		
39x13.50R17/D	121R	M + S, 3PMSF	50K	RBL	52341	8.5 - 11	13.5 on 11	38.5	15	540	3195@50		
33x12.50R18/E	118S	M + S, 3PMSF	50K	RBL	27247	8.5 - 11	12.5 on 10	32.5	15	640	2910@65		
34x12.50R18/E	121R	M + S, 3PMSF	50K	RBL	36312	8.5 - 11	12.5 on 10	33.5	15	621	3195@65		
35x12.50R18/E	123R	M + S, 3PMSF	50K	RWL	13389	8.5 - 11	12.5 on 10	34.5	15	602	3415@65		
33x12.50R20/E	114S	M + S, 3PMSF	50K	RBL	04929	8.5 - 11	12.5 on 10	32.5	15	640	2600@65		
35x12.50R20/E	121R	M + S, 3PMSF	50K	RBL	23413	8.5 - 11	12.5 on 10	34.5	15	602	3195@75		
37x12.50R20/E	126R	M + S, 3PMSF	50K	RBL	18629	8.5 - 11	12.5 on 10	36.5	15	569	3750@75		
33x12.50R22/E	109R	M + S, 3PMSF	50K	RBL	62273	8.5 - 11	12.5 on 10	32.5	15	640	2270@65		
35x12.50R22/E	117R	M + S, 3PMSF	50K	RBL	67480	8.5 - 11	12.5 on 10	34.5	15	602	2835@65		
LT215/75R15/C	100/97S	M + S, 3PMSF	50K	RBL	44092	5.5 - 7	8.5 on 6	27.7	15	751	1765@50		
LT235/75R15/C	104/101S	M + S, 3PMSF	50K	RWL	63647	6 - 7	9.3 on 6.5	28.9	15	721	1985@50		
LT215/65R16/D	103/100S	M + S, 3PMSF	50K	RBL	93878	6 - 7.5	8.7 on 6.5	27	13	770	1930@65		
LT215/70R16/C	100/97R	M + S, 3PMSF	50K	RWL	56039	5.5 - 7	8.7 on 6.5	27.9	15	746	1765@50		
LT225/70R16/C	102/99R	M + S, 3PMSF	50K	RWL	94668	6 - 7	9 on 6.5	28.4	15	732	1875@50		
LT225/75R16/E	115/112S	M + S, 3PMSF	50K	RWL	37527	6 - 7	8.8 on 6	29.3	15	710	2680@80		
LT235/70R16/C	104/101S	M + S, 3PMSF	50K	RWL	33403	6 - 7.5	9.5 on 7	29	15	718	1985@50		
LT235/85R16/E	120/116S	M + S, 3PMSF	50K	RWL	75445	6 - 7.5	9.3 on 6.5	31.7	15	656	3042@80		
LT245/70R16/D	113/110S	M + S, 3PMSF	50K	RWL	28855	6.5 - 7	9.8 on 7	29.5	15	704	2535@65		
LT245/75R16/E	120/116S	M + S, 3PMSF	50K	RWL	15477	6.5 - 8	9.8 on 7	30.5	15	683	3042@80		
LT255/70R16/E	120/117S	M + S, 3PMSF	50K	RWL	65289	6.5 - 8	10.2 on 7.5	30.1	15	691	3085@80		
LT265/70R16/E	121/118S	M + S, 3PMSF	50K	RWL	62023	7 - 8.5	10.7 on 8	30.6	15	679	3195@80		
LT265/75R16/E	123/120R	M + S, 3PMSF	50K	RWL	67179	7 - 8	10.5 on 7.5	31.7	15	657	3415@80		
LT275/70R16/D	119/116S	M + S, 3PMSF	50K	RWL	97884	7 - 8.5	11 on 8	31.2	15	667	3000@65		
LT285/75R16/E	126/123R	M + S, 3PMSF	50K	RWL	05855	7.5 - 9	11.3 on 8	32.8	15	634	3750@80		
LT295/75R16/E	128/125R	M + S, 3PMSF	50K	RWL	99926	7.5 - 9.5	11.6 on 8	33.4	15	623	3970@80		
LT305/70R16/E	124/121R	M + S, 3PMSF	50K	RWL	34102	8 - 9.5	12.2 on 9	32.8	15	634	3525@65		
LT315/75R16/E	127/124R	M + S, 3PMSF	50K	RWL	50203	8 - 11	12.3 on 8.5	34.6	15	602	3860@65		
LT225/65R17/D	107/103S	M + S, 3PMSF	50K	RBL	95341	6 - 8	9 on 6.5	28.5	13	730	2150@65		
LT235/80R17/E	120/117S	M + S, 3PMSF	50K	RBL	10158	6 - 7.5	9.3 on 6.5	31.8	15	654	3085@80		
LT245/65R17/D	111/108S	M + S, 3PMSF	50K	RWL	52433	7 - 8	9.8 on 7	29.5	13	704	2405@65		

Light Truck/SUV

Continued ►

See Important Product Information section at the back of the book.

BFGOODRICH® ALL-TERRAIN T/A® KO2

Tire Size	Service Description	Other	Limited Warranty	Side-wall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width (inches)	Overall Diameter (inches)	Tread Depth (in/32nds)	Rev/ Mile @45 mph	Max Load Single (lbs@psi)	UTQG	OE FITMENTS
LT245/70R17/E	119/116S	M + S, 3PMSF	50K	RWL	09666	6.5 - 8	9.8 on 7	30.6	15	681	3000@80		
LT245/75R17/E	121/118S	M + S, 3PMSF	50K	RWL	26470	6.5 - 7.5	9.8 on 7	31.5	15	660	3195@80		
LT255/65R17/D	114/110S	M + S, 3PMSF	50K	RWL	28221	7 - 9	10.2 on 7.5	30.1	15	691	2600@65		
LT255/70R17/E	121/118S	M + S, 3PMSF	50K	RBL	37495	6.5 - 8.5	10.2 on 7.5	31.1	15	669	3195@80		
LT255/75R17/C	111/108S	M + S, 3PMSF	50K	RBL	11450	6.5 - 8.5	10 on 7	32.1	15	649	2405@50		
LT265/65R17/E	120/117S	M + S, 3PMSF	50K	RWL	16681	7.5 - 9.5	10.7 on 8	30.6	15	681	3085@80		
LT265/70R17/C	112/109S	M + S, 3PMSF	50K	RWL	66255	7 - 8.5	10.7 on 8	31.7	15	657	2470@50		
LT265/70R17/C	112/109S	M + S, 3PMSF	50K	RBL	10892	7 - 8.5	10.7 on 8	31.7	15	657	2470@50		JEP/FOR
LT265/70R17/E	121/118S	M + S, 3PMSF	50K	RWL	29668	7 - 8.5	10.7 on 8	31.7	15	657	3195@80		
LT275/65R17/E	121/118S	M + S, 3PMSF	50K	RWL	42347	7.5 - 9.5	11 on 8	31.1	15	669	3195@80		
LT275/70R17/E	121/118R	M + S, 3PMSF	50K	RWL	85924	7 - 8.5	11 on 8	32.2	15	646	3195@80		
LT285/70R17/C	116/113Q	M + S, 3PMSF	50K	RBL	81501	7.5 - 9	11.5 on 8.5	32.8	15	635	2755@50		JEP
LT285/70R17/C	116/113Q	M + S, 3PMSF	50K	RWL	31812	7.5 - 9	11.5 on 8.5	32.8	15	635	2755@50		JEP
LT285/70R17/C	116/113S	M + S, 3PMSF	50K	RBL	24481	7.5 - 9	11.5 on 8.5	32.8	15	635	2755@50		FOR
LT285/70R17/E	121/118R	M + S, 3PMSF	50K	RWL	99728	7.5 - 9	11.5 on 8.5	32.8	15	635	3195@80		
LT285/75R17/E	121/118S	M + S, 3PMSF	50K	RBL	74713	7.5 - 9.5	11.3 on 8	33.9	15	614	3195@80		
LT295/70R17/E	121/118S	M + S, 3PMSF	50K	RWL	69195	7.5 - 10	11.8 on 8.5	33.3	15	624	3195@80		
LT305/65R17/E	121/118R	M + S, 3PMSF	50K	RWL	00819	8.5 - 11	12.2 on 9	32.6	15	638	3195@65		
LT315/70R17/C	113/110T	M + S, 3PMSF	50K	RBL	07361	8 - 11	12.7 on 9.5	34.4	15	604	2535@45		FOR
LT315/70R17/E	121/118S	M + S, 3PMSF	50K	RBL	08806	8 - 11	12.7 on 9.5	34.4	15	604	3195@65		
LT255/55R18/D	109/105R	M + S, 3PMSF	50K	RBL	04785	7 - 9	10.4 on 8	29	13	717	2270@65		
LT255/70R18/D	117/114S	M + S, 3PMSF	50K	RBL	70539	6.5 - 8.5	10.2 on 7.5	32.1	15	648	2835@65		
LT265/60R18/E	119/116S	M + S, 3PMSF	50K	RBL	63681	7.5 - 9.5	10.7 on 8	30.5	15	682	3000@80		
LT265/65R18/E	122/119R	M + S, 3PMSF	50K	RWL	05260	7.5 - 9.5	10.7 on 8	31.5	15	659	3305@80		
LT265/70R18/E	124/121R	M + S, 3PMSF	50K	RWL	40855	7 - 9	10.7 on 8	32.6	15	637	3525@80		
LT275/65R18/E	123/120R	M + S, 3PMSF	50K	RWL	19463	7.5 - 9	11 on 8	32.1	15	648	3415@80		
LT275/70R18/E	125/122R	M + S, 3PMSF	50K	RWL	45062	7 - 8.5	11 on 8	33.2	15	627	3640@80		
LT285/60R18/D	118/115S	M + S, 3PMSF	50K	RWL	99506	8 - 10	11.5 on 8.5	31.5	15	661	2910@65		
LT285/65R18/E	125/122R	M + S, 3PMSF	50K	RWL	16168	8 - 10	11.5 on 8.5	32.6	15	639	3640@80		
LT305/65R18/E	124/121R	M + S, 3PMSF	50K	RBL	07337	8.5 - 11	12.2 on 9	33.6	15	619	3525@65		
LT305/70R18/E	126/123R	M + S, 3PMSF	50K	RBL	02293	8.5 - 10	12.2 on 9	34.8	15	597	3750@75		
LT325/65R18/E	127/124R	M + S, 3PMSF	50K	RWL	01547	9 - 12	13 on 9.5	34.6	15	601	3860@65		
LT265/60R20/E	121/118S	M + S, 3PMSF	50K	RBL	85528	7.5 - 9.5	10.7 on 8	32.5	15	640	3195@80		
LT275/55R20/D	115/112S	M + S, 3PMSF	50K	RBL	61764	7.5 - 9.5	11.2 on 8.5	31.9	15	652	2680@65		
LT275/60R20/D	119/116S	M + S, 3PMSF	50K	RBL	64811	7.5 - 9.5	11 on 8	33	15	630	3000@65		
LT275/65R20/E	126/123S	M + S, 3PMSF	50K	RBL	17764	7.5 - 9.5	11 on 8	34.1	15	610	3750@80		
LT285/55R20/D	117/114T	M + S, 3PMSF	50K	RBL	36614	8 - 10	11.7 on 9	32.4	15	643	2835@65		
LT285/60R20/E	125/122S	M + S, 3PMSF	50K	RBL	29598	8 - 10	11.5 on 8.5	33.5	15	622	3640@80		
LT285/65R20/E	127/124S	M + S, 3PMSF	50K	RBL	02279	8 - 10	11.5 on 8.5	34.6	15	602	3860@80		
LT295/55R20/E	123/120R	M + S, 3PMSF	50K	RBL	62900	8 - 10	12.2 on 9.5	32.8	15	635	3415@80		
LT295/60R20/E	126/123R	M + S, 3PMSF	50K	RBL	33830	8 - 10	11.8 on 8.5	33.9	15	613	3750@80		
LT295/65R20/E	129/126R	M + S, 3PMSF	50K	RBL	05511	8 - 10	11.8 on 8.5	35.1	15	592	4080@80		
LT305/55R20/E	121/118S	M + S, 3PMSF	50K	RBL	15149	8.5 - 11	12.4 on 9.5	33.2	15	626	3195@65		
LT325/60R20/E	126/123S	M + S, 3PMSF	50K	RBL	12201	9 - 12	13 on 9.5	35.4	15	588	3750@75		