

BFGOODRICH® TRAIL-TERRAIN T/A®

Adventure-ready when you need it.



ALL-SEASON



BENEFITS OF BFGOODRICH® TIRES

BUILT TO LAST: The BFGoodrich® Trail-Terrain T/A® tire outlasts the Cooper® Discoverer® AT3 4S™ tire by more than 4,500 miles¹.

The all-new BFGoodrich® Trail-Terrain T/A® tire is backed by a 60,000-Mile Warranty and 60-Day Satisfaction Guarantee². An optimized footprint design featuring Full-Depth 3-D Locking Sipes provides excellent tread block stability for even wear, which results in longer tread life and a quiet, comfortable ride.

EQUIPPED FOR EVERY SEASON: The BFGoodrich® Trail-Terrain T/A® tire offers 11% better snow traction than the Cooper® Discoverer® AT3 4S™ tire³.

Don't let adverse weather stand in your way. The BFGoodrich® Trail-Terrain T/A® tire is severe snow rated with a three-peak mountain snowflake symbol. It continues to provide traction long after the mercury drops. The Full-Depth 3-D Sipes are engineered to create plenty of power and grip over the full life of the tire.

ENGINEERED TO EXPLORE: The good road in isn't always the good road out.

It's not your average daily driver. The BFGoodrich® Trail-Terrain T/A® tire is designed to resist chipping and tearing in occasional gravel road usage. The serrated shoulder design is optimized for soft-soil traction in light off-pavement situations without compromising road noise.

60-DAY SATISFACTION GUARANTEE

60-Day Satisfaction Guarantee⁴.

We're confident you'll love your new BFGoodrich® Trail-Terrain T/A® replacement tires. So confident, in fact, that we back your purchase with a 60-Day Satisfaction Guarantee. If you're not 100% satisfied with your new tires, just bring the tires and original sales receipt back to the place where you bought the tires within 60 days of your purchase and we will gladly exchange them for a new set of tires of equal or lesser value.

¹Based on a treadwear test using tires in size 265/70R17 115T on a 2020 Ford F150 4x4. Actual on-road results may vary.

²Guarantee applies to up to 6 tires per customer. Guarantee applies only to tires that were purchased and mounted and does not apply to exchanged tires that were provided under this guarantee. The guarantee does not include the cost of valve stems. Tires that are damaged due to misuse or misapplication, road hazards, mechanical problems related to the vehicle, use in any racing-related activities, or competitive events or tires that are removed from the original vehicle on which they were installed are excluded from guarantee.

³Based on third-party snow traction tests using ASTM Test Method F1805-12, using tires in size 265/70R17 115T. Actual on-road results may vary.

⁴Guarantee applies to up to 6 tires per customer. Guarantee applies only to tires that were purchased and mounted and does not apply to exchanged tires that were provided under this guarantee. The guarantee does not include the cost of valve stems. Tires that are damaged due to misuse or misapplication, road hazards, mechanical problems related to the vehicle, use in any racing-related activities, or competitive events or tires that are removed from the original vehicle on which they were installed are excluded from guarantee.



WEAR LIFE



FUEL EFFICIENCY



OFF-ROAD



BRAKING



COMFORT

POPULAR REPLACEMENT MARKET FITMENTS:

Chevrolet Silverado 1500
Ford Bronco Sport
Ford Ranger
Jeep Renegade & Cherokee
Subaru Outback
Toyota RAV4
Toyota Tacoma



Experienced driver depicted.

BFGOODRICH® TRAIL-TERRAIN T/A®

Tire Size	Service Description	Other	Limited Warranty	Side-wall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width (inches)	Overall Diameter (inches)	Tread Depth (in/32nds)	Rev/Mile @45 mph	Max Load Single (lbs@psi)	UTQG
235/75R15/XL	109T	M + S, 3PMSF	60K	ORWL	12184	6 - 8	9.2 on 6.5	28.9	12.5	721	2271@50	660/A/A
225/75R16/XL	108T	M + S, 3PMSF	60K	ORWL	06260	6 - 7.5	8.9 on 6	29.3	12.5	710	2205@50	660/A/A
265/70R16	112T	M + S, 3PMSF	60K	ORWL	10385	7 - 9	10.7 on 8	30.6	12.5	679	2469@44	660/A/A
215/65R17	99T	M + S, 3PMSF	60K	ORWL	01727	6 - 7.5	8.7 on 6.5	28	12.5	742	1709@44	660/A/A
225/65R17	102T	M + S, 3PMSF	60K	ORWL	92893	6 - 8	9 on 6.5	28.5	12.5	730	1874@44	660/A/A
235/65R17/XL	108T	M + S, 3PMSF	60K	ORWL	56199	6.5 - 8.5	9.4 on 7	29.1	12.5	716	2205@50	660/A/A
245/65R17/XL	111T	M + S, 3PMSF	60K	ORWL	01614	7 - 8.5	9.8 on 7	29.5	12.5	704	2403@50	660/A/A
245/70R17/XL	114T	M + S, 3PMSF	60K	ORWL	67462	6.5 - 8	9.8 on 7	30.5	12.5	681	2601@50	660/A/A
245/75R17	112T	M + S, 3PMSF	60K	ORWL	06073	6.5 - 8	9.8 on 7	31.5	12.5	660	2469@44	660/A/A
255/65R17	110T	M + S, 3PMSF	60K	ORWL	78163	7 - 9	10.2 on 7.5	30.1	12.5	691	2337@44	660/A/A
265/65R17	112T	M + S, 3PMSF	60K	ORWL	01542	7.5 - 9.5	10.7 on 8	30.5	12.5	681	2469@44	660/A/A
265/70R17	115T	M + S, 3PMSF	60K	ORWL	71447	7 - 9	10.7 on 8	31.6	12.5	657	2679@44	660/A/A
P285/70R17	117T	M + S, 3PMSF	60K	ORWL	08164	7.5 - 9.5	11.5 on 8.5	32.8	12.5	635	2833@44	660/A/B
225/55R18/XL	102H	M + S, 3PMSF	60K	BSW	20173	6 - 8	9.2 on 7	27.8	12.5	749	1874@50	660/A/A
235/55R18/XL	104H	M + S, 3PMSF	60K	BSW	07789	6.5 - 8.5	9.6 on 7.5	28.1	12.5	739	1984@50	660/A/A
235/60R18/XL	107H	M + S, 3PMSF	60K	BSW	17722	6.5 - 8.5	9.4 on 7	29.1	12.5	715	2150@50	660/A/A
255/55R18/XL	109H	M + S, 3PMSF	60K	BSW	39545	7 - 9	10.4 on 8	29	12.5	717	2271@50	660/A/A
255/65R18	111T	M + S, 3PMSF	60K	ORWL	78303	7 - 9	10.2 on 7.5	31.1	12.5	670	2403@44	660/A/A
255/70R18/XL	116H	M + S, 3PMSF	60K	BSW	68498	6.5 - 8.5	10.2 on 7.5	32.1	12.5	648	2756@50	660/A/A
265/60R18	110T	M + S, 3PMSF	60K	ORWL	92079	7.5 - 9.5	10.7 on 8	30.5	12.5	682	2337@44	660/A/A
265/65R18	114T	M + S, 3PMSF	60K	ORWL	57310	7.5 - 9.5	10.7 on 8	31.5	12.5	659	2601@44	660/A/A
265/70R18	116T	M + S, 3PMSF	60K	ORWL	75198	7 - 9	10.7 on 8	32.6	12.5	637	2756@44	660/A/A
275/65R18	116T	M + S, 3PMSF	60K	ORWL	95912	7.5 - 9.5	11 on 8	32.1	12.5	648	2756@44	660/A/A
285/60R18	116H	M + S, 3PMSF	60K	BSW	50153	8 - 10	11.5 on 8.5	31.5	12.5	661	2756@51	660/A/A
255/55R20/XL	110H	M + S, 3PMSF	60K	BSW	59755	7 - 9	10.4 on 8	31	12.5	671	2337@50	660/A/A
265/50R20	107H	M + S, 3PMSF	60K	BSW	04147	7.5 - 9.5	10.9 on 8.5	30.5	12.5	683	2150@51	660/A/A
275/55R20	113T	M + S, 3PMSF	60K	ORWL	09185	7.5 - 9.5	11.2 on 8.5	31.9	12.5	652	2535@44	660/A/A
275/60R20	115T	M + S, 3PMSF	60K	ORWL	40750	7.5 - 9.5	11 on 8	33	12.5	630	2679@44	660/A/A
275/45R22/XL	112H	M + S, 3PMSF	60K	BSW	34341	8.5 - 10.5	10.7 on 9	31.8	12.5	655	2469@50	660/A/A
285/45R22/XL	114H	M + S, 3PMSF	60K	BSW	56955	9 - 10.5	11.2 on 9.5	32.1	12.5	648	2601@50	660/A/A

Light Truck/SUV