

Off-Road

The **Discoverer STT Pro** tire delivers off-road performance, empowering the extreme off-roader to take on the toughest challenges.

- Patented Armor Tek³® tire technology adds strength to the tire sidewall
- Rubber formulated to combat shredding and damage from stones and off-road obstacles
- Tread pattern designed to get you through extreme off-road trails



45-DAY Test Drive*



Mud Slingers™ 2.0

Deep, wide trenches with additional notches to help power through thick mud and help continuously clear mud from the tread.

Earth Diggers™ Technology

Tackle tricky terrain with large blocks with alternating mud scoops that forcefully dig into loose dirt, sand or sticky mud.

Rock Climber Sidewall™ Technology

Tackle tough obstacles with deep “climber cleats” and flex grooves built into the side of the tire that grip jagged rocks and power through thick mud.

Stone Armor™ Technology

Provides the ultimate durability with channels, ridges, and edges designed to help defend against sharp rocks and debris while expelling lodged stones.

ALL-TERRAIN

Discoverer® STT Pro™

Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Widths (Inches)	Measuring Rim Width (Inches)	Section Width (Inches)	Overall Diameter (Inches)	Max Load (Lbs)	Tread Depth (in 32nds)	Revs / Mile
Discoverer STT Pro												
30X9.50R15LT	104Q	C	RWL	170122034	245210	6.5 - 8.5	7.5	9.6	29.6	1985	19	701
31X10.50R15LT	109Q	C	RWL	170110034	245197	7.0 - 9.0	8.5	10.7	30.8	2270	20	674
32X11.50R15LT	113Q	C	RWL	170130034	245228	8.0 - 10.0	9.0	11.7	31.6	2535	20	657
33X12.50R15LT	108Q	C	RWL	170107034	245070	8.5 - 11.0	10.0	12.2	32.7	2205	21	634
35X12.50R15LT	113Q	C	RWL	170113034	245201	8.5 - 11.0	10.0	13.1	34.6	2535	21	600
LT215/85R16	115Q	E	BLK	170126006	245224	5.5 - 7.0	6.0	8.5	30.6	2680	18	678
LT235/85R16	120Q	E	BLK	170109006	245196	6.0 - 7.5	6.5	9.6	31.9	3042	18	650
LT245/75R16	120Q	E	BLK	170112006	245200	6.5 - 8.0	7.0	9.6	30.7	3042	18	675
LT265/75R16	123Q	E	RWL	170106034	245069	7.0 - 8.0	7.5	10.7	31.9	3415	18	650
LT285/75R16	126Q	E	RWL	170108034	245195	7.5 - 9.0	8.0	11.2	33.0	3750	19	628
LT305/70R16	124Q	E	RWL	170120034	245208	8.0 - 9.5	9.0	12.3	33.0	3525	19	628
LT315/75R16	127Q	E	RWL	170117034	245205	8.0 - 11.0	8.5	12.6	34.5	3860	20	600
35X12.50R17LT	121Q	E	RWL	170255034	254421	8.5 - 11.0	10.0	12.6	34.6	3195	21	600
37X12.50R17LT	124Q	D	BLK	170129006	245227	8.5 - 11.0	10.0	13.0	36.8	3525	22	564
37X13.50R17LT	121Q	E	BLK	170137006	245304	8.5 - 11.0	11.0	13.3	36.8	3195	22	564
40X13.50R17LT	121Q	C	BLK	170142006	245355	8.5 - 11.0	11.0	13.6	39.8	3195	22	521
LT265/70R17	121Q	E	RWL	170102034	244997	7.0 - 8.5	8.0	10.7	31.9	3195	18	649
LT285/70R17	121Q	E	RWL	170114034	245202	7.5 - 9.0	8.5	11.5	33.0	3195	19	628
LT295/70R17	121Q	E	RWL	170115034	245203	7.5 - 10.0	8.5	12.0	33.5	3195	21	620
LT305/65R17	121Q	E	BLK	170136006	245302	8.5 - 11.0	9.0	12.3	32.7	3195	21	634
LT315/70R17	121Q	E	RWL	170119034	245207	8.0 - 11.0	9.5	12.6	34.6	3195	21	600
35X12.50R18LT	118Q	D	BLK	170229006	246689	8.5 - 11.0	10.0	12.7	34.6	2910	21	599
37X13.50R18LT	124Q	D	BLK	170139006	245310	8.5 - 11.0	11.0	13.3	36.8	3525	22	564
LT275/65R18	123Q	E	RWL	170121034	245209	7.5 - 9.0	8.0	10.9	32.3	3415	19	642
LT275/70R18	125P	E	RWL	170111034	245199	7.0 - 9.0	8.0	11.3	33.3	3640	20	622
LT285/65R18	125Q	E	RWL	170118034	245206	8.0 - 10.0	8.5	11.8	32.9	3640	19	630
LT295/70R18	129P	E	RWL	170145034	245367	7.5 - 10.0	8.5	12.0	34.5	4080	21	601
LT305/60R18	121Q	E	RWL	170123034	245221	8.5 - 11.0	9.0	12.0	32.7	3195	21	634
LT305/60R18	126Q	F	RWL	170147034	245375	8.5 - 11.0	9.0	12.0	32.7	3750	21	634
LT305/70R18	126Q	E	RWL	170125034	245223	8.5 - 10.0	9.0	12.4	35.1	3750	21	591
LT325/65R18	127Q	E	RWL	170124034	245222	9.0 - 12.0	9.5	13.7	34.7	3860	21	598
33X12.50R20LT	119Q	F	BLK	170230006	246690	8.5 - 11.0	10.0	12.5	32.8	3000	21	633
35X12.50R20LT	121Q	E	BLK	170128006	245226	8.5 - 11.0	10.0	12.4	34.7	3195	21	598
35X12.50R20LT	125Q	F	BLK	170148006	245382	8.5 - 11.0	10.0	12.4	34.7	3640	21	598
37X12.50R20LT	126Q	E	BLK	170138006	245307	8.5 - 11.0	10.0	12.6	36.7	3750	21	565
35X13.50R20LT	121Q	E	BLK	170141006	245352	8.5 - 11.0	11.0	13.2	34.6	3195	21	600
37X13.50R20LT	127Q	E	BLK	170134006	245246	8.5 - 12.0	11.0	13.3	36.9	3860	21	563
38X13.50R20LT	123Q	D	BLK	170143006	245359	8.5 - 11.0	11.0	13.6	38.2	3415	21	543
38X15.50R20LT	128Q	E	BLK	170144006	245364	11.0 - 13.0	12.0	15.4	37.8	3970	21	548
LT275/65R20	121Q	D	BLK	170159006	245403	7.5 - 9.5	8.0	10.9	34.5	3195	19	601
LT275/65R20	126Q	E	BLK	170127006	245225	7.5 - 9.5	8.0	10.9	34.5	3750	19	601
LT295/55R20	123Q	E	BLK	170135006	245301	8.0 - 10.0	9.5	12.3	33.1	3415	20	627
LT295/60R20	126Q	E	BLK	170104006	245067	8.0 - 10.0	8.5	11.5	34.3	3750	19	605
LT295/65R20	129Q	E	BLK	170105006	245068	8.0 - 10.0	8.5	11.7	35.4	4080	19	585
LT305/55R20	125Q	F	BLK	170146006	245371	8.5 - 11.0	9.5	12.4	33.5	3640	20	619
35X12.50R22LT	121Q	F	BLK	170231006	246691	8.5 - 11.0	10.0	12.3	34.8	3195	21	596
37X13.50R22LT	123Q	E	BLK	170140006	245351	8.5 - 12.0	11.0	13.4	36.9	3415	21	562

For dual max load and spacing, please call the Cooper Tire Consumer Relations Department for a proper fitment recommendation.

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels; this may result in serious injury or death.

NOTE: When replacing a vehicle's original equipment light truck tires with passenger car tires, the load on each replacement car tire must not exceed the maximum load stamped on the replacement car tire sidewall divided by 1.10.