

DESTINATION™ X/T

ALL-WEATHER, ALL-TERRAIN



NEVER BACK DOWN FROM CHALLENGING TERRAIN

Features & Benefits



Masters muddy terrain to help prevent slipping, spinning or getting stuck



Delivers confident off-road traction in wet conditions



3-Peak Mountain Snowflake Certified



On-Road Wet Performance

50,000
MILE LIMITED WARRANTY*



Staggered Shoulder Lugs

and an aggressive off-shoulder tread design provide extra biting edges for off-road performance

Full-Depth Interlocking 3D Sipe Technology

helps to provide even wear and consistent performance through the limited mileage warranty period

Open Shoulder Slots

provide off-road traction and also evacuate water to help reduce the risk of hydroplaning

* Conditions apply. See FirestoneTire.com/warranty for details.

Firestone



Top Fitments

- Chevrolet Silverado
- Ford F-250
- Ford F-350
- GMC Sierra
- Jeep Wrangler Rubicon

Warranty†

- 50,000 Mile Limited Warranty
- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



Tire Specifications

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Minimum Dual Spacing	Revs Per Mile	UTQG	Wt.
15" Rim Diameter												
30X9.50R15LT 104R	C	006133	OWL	6.5-8.5	7.5	29.5	9.5	14	-	706	-	36
31X10.50R15LT 109R	C	004389	OWL	7.0-9.0	8.5	30.5	10.5	15	-	683	-	41
33X12.50R15LT 108R	C	006134	OWL	8.5-11.0	10.0	32.5	12.5	17	-	641	-	51
16" Rim Diameter												
LT215/85R16 115/112S	E	004388	BW	5.5-7.0	6.0	30.4	8.5	14	9.9	685	-	37
LT235/85R16 120/116S	E	004381	BW	6.0-7.5	6.5	31.7	9.3	14	10.8	666	-	40
LT225/75R16 115/112S	E	004379	BW	6.0-7.0	6.0	29.3	8.8	14	10.2	711	-	35
LT245/75R16 120/116S	E	004374	BW	6.5-8.0	7.0	30.5	9.8	14	11.3	684	-	39
LT265/75R16 123/120S	E	004376	OWL	7.0-8.0	7.5	31.7	10.5	15	12.2	658	-	45
LT285/75R16 126/123R	E	009608	OWL	7.5-9.0	8.0	32.8	11.3	16	13.1	634	-	52
17" Rim Diameter												
LT235/80R17 120/117S	E	004384	BW	6.0-7.5	6.5	31.8	9.3	14	10.8	655	-	40
LT245/75R17 121/118S	E	004375	OWL	6.5-7.5	7.0	31.5	9.8	14	11.3	661	-	42
LT255/75R17 111/108T	C	004393	BW	6.5-8.5	7.0	32.1	10.0	15	11.7	650	-	41
LT285/75R17 121/118S	D	013922	BW	7.5-9.5	8.0	33.9	11.3	16	-	615	-	54
LT245/70R17 119/116S	E	004385	OWL	6.5-8.0	7.0	30.6	9.8	14	11.3	682	-	42
LT265/70R17 121/118S	E	004373	OWL	7.0-8.5	8.0	31.7	10.7	15	12.4	658	-	46
LT275/70R17 121/118R	E	008381	OWL	7.0-8.5	8.0	32.2	11.0	16	12.8	647	-	49
LT285/70R17 121/118S	E	004383	BW	7.5-9.0	8.5	32.8	11.5	16	13.4	636	-	50
LT305/70R17 121/118R	E	013918	BW	8.0-9.5	9.0	33.8	12.2	16	-	616	-	58
LT315/70R17 121/118R	E	006135	OWL	8.5-10.0	9.5	34.4	12.7	17	14.8	605	-	61
LT265/65R17 120/117S	E	013926	BW	7.5-9.5	8.0	30.6	10.7	12	-	682	-	44
18" Rim Diameter												
33X12.50R18LT 118S	E	013916	BW	8.5-11.0	10.0	32.5	12.5	17	-	641	-	55
35X12.50R18LT 123R	E	006412	OWL	8.5-11.0	10.0	34.5	12.5	17	-	603	-	60
LT265/70R18 124/121S	E	004386	BW	7.0-9.0	8.0	32.6	10.7	15	12.4	638	-	47
LT275/70R18 125/122S	E	004377	OWL	7.0-8.5	8.0	33.2	11.0	16	12.8	628	-	50
LT265/65R18 122/119S	E	015058	BW	7.5-9.5	8.0	31.6	31.6	12	-	657	-	46
LT275/65R18 123/120S	E	004380	OWL	7.5-9.0	8.0	32.1	11.0	16	12.8	649	-	49
LT285/65R18 125/122R	E	008375	BW	8.0-10.0	8.5	32.6	11.5	16	13.4	640	-	50

Tire Specifications Legend

New sizes

* OEM Tire	OWL Outline White Letter	~ Pinned for #12 Stud Sizes
¥ MOE (Mercedes Exclusive)	RBL Raised Black Letter	f Pinned for #15 Stud Sizes
^ RFT (Run Flat Tire)	XL Extra Load (XL)	** Pinned for #16 Stud Sizes
BW Blackwall	◆ Pinned for #11 Stud Sizes	*** Pinned for #17 Stud Sizes

Tire Size and Service Description	Load Range	Item Number	Sidewall Styling	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Depth (32nd)	Minimum Dual Spacing	Revs Per Mile	UTQG	Wt.
20" Rim Diameter												
35X12.50R20LT 121R	E	006132	OWL	8.5-11.0	10.0	34.5	12.5	17	-	603	-	60
LT275/65R20 126/123S	E	004382	OWL	7.5-9.5	8.0	34.1	11.0	16	12.8	611	-	53
LT285/65R20 127/124S	E	008386	BW	8.0-10.0	8.5	34.6	11.5	16	13.4	603	-	53
LT265/60R20 121/118S	E	004392	BW	7.5-9.5	8.0	32.5	10.7	15	12.4	641	-	48
LT275/60R20 123/120R	E	008383	BW	7.5-9.5	8.0	33.0	11.0	16	12.8	631	-	52
LT285/60R20 125/122S	E	004390	BW	8.0-10.0	8.5	33.5	11.5	16	13.4	623	-	53
LT295/60R20 126/123S	E	008388	BW	8.0-10.0	8.5	33.9	11.8	16	13.7	614	-	57
LT275/55R20 120/117R	E	008380	BW	7.5-9.5	8.5	31.9	11.2	16	13.0	653	-	49
LT285/55R20 122/119R	E	008376	BW	8.0-10.0	9.0	32.4	11.7	16	13.6	644	-	53
LT305/55R20 121/118R	E	008377	BW	8.5-11.0	9.5	33.2	12.4	16	14.5	627	-	57