



LT/SUV | ALL-SEASON | ALL-TERRAIN

GRABBER A/T^X

Rim Diameter



14" - 22"

Aspect Ratio



45 - 85
(& Widths 8.50 - 13.50)

Tread Pattern



Symmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED	WARRANTY
640 (Metric)	A	B	S & T	60,000 Miles
-- (LT)	--	--	Q & R	50,000 Miles

Benefits

- Balanced off-road traction with on-road performance
- Robust strength and durability
- Aggressive styling
- Low road noise
- Long-lasting treadwear



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.



DURAGEN
EG
TECHNOLOGY

- Enhances strength and durability
- Delivers cut-and-chip resistance
- Extends tread life



3-Peak Mountain Snowflake

Meets the severe snow service requirements of the U.S. Tire Manufacturers Association (USTMA) and the Tire and Rubber Association of Canada (TRAC).



Pinned for Winter Studs

Stud length for metric sizes: 12mm (TSMI #13). Stud size listed on the tire's sidewall.

Sample Vehicle Fitments Include:

- Chevrolet: Silverado, Silverado HD & Tahoe
- Ford: Bronco, Explorer, F-150 & Super Duty
- Jeep: Gladiator, Grand Cherokee & Wrangler
- Nissan: Frontier, Pathfinder & Titan
- Ram: Pickup Trucks
- Toyota: 4Runner, Tacoma & Tundra

GRABBER A/T^X | Product Data

LT/SUV | ALL-SEASON | ALL-TERRAIN

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
14	8.50	27 X 8.50 R 14 LT	95 Q	C	RWL	04508120000	Yes	27.0	30.9	50.0	8.6 (7.0)	(6.0 - 7.5)	1520	16	769
	9.50	30 X 9.50 R 15 LT	104 S	C	RWL	04508400000	Yes	30.0	38.5	50.0	9.4 (7.5)	(6.5 - 8.5)	1984	16	692
	10.50	31 X 10.50 R 15 LT	109 S	C	RWL	04505590000	Yes	31.0	45.7	50.0	10.6 (8.5)	(7.0 - 9.0)	2270	17	670
	12.50	33 X 12.50 R 15 LT	108 R	E	RWL	04494910000	Yes	15.0	56.9	36.0	12.5 (10.0)	(8.5 - 11.0)	2205	17	1385
	70	225/70 R 15	100 T	SL	RWL	04504110000	Yes	27.4	31.3	44.0	9.0 (6.5)	(6.0 - 7.5)	1764	14	758
	70	265/70 R 15	112 T	SL	RWL	04504080000	Yes	29.6	38.6	44.0	10.7 (8.0)	(7.0 - 9.0)	2469	14	702
	75	205/75 R 15	97 T	SL	RWL	04503590000	Yes	27.1	28.5	44.0	8.0 (5.5)	(5.0 - 7.0)	1609	14	766
	75	215/75 R 15	100 T	SL	RWL	04503850000	Yes	27.7	31.5	44.0	8.5 (6.0)	(5.5 - 7.0)	1764	14	750
	75	LT235/75 R 15	104/101 S	C	RWL	04507270000	Yes	28.9	36.6	50.0	9.3 (6.5)	(6.0 - 7.0)	1985	17	719
16	65	215/65 R 16	98 T	SL	BSW	04503600000	Yes	27.0	29.7	44.0	8.7 (6.5)	(6.0 - 7.5)	1653	14	769
	70	215/70 R 16	100 T	SL	RWL	04503610000	Yes	27.9	31.0	44.0	8.7 (6.5)	(5.5 - 7.0)	1764	14	746
	70	255/70 R 16	111 T	SL	RWL	04504000000	Yes	30.1	39.7	44.0	10.2 (7.5)	(6.5 - 8.5)	2403	14	691
	70	265/70 R 16	112 T	SL	RWL	04509710000	Yes	30.6	41.3	44.0	10.7 (8.0)	(7.0 - 9.0)	2469	14	679
	70	LT305/70 R 16	124/121 R	E	RWL	04506790000	Yes	32.8	62.6	65.0	12.2 (9.0)	(8.0 - 9.5)	3525	16	633
	75	LT245/75 R 16	120/116 R	E	RWL	04494740000	Yes	30.5	46.8	80.0	9.8 (7.0)	(6.5 - 8.0)	3085	17	682
	75	LT245/75 R 16	120/116 R	E	RWL	04508460000	Yes	30.5	48.1	80.0	9.8 (7.0)	(6.5 - 8.0)	3086	16	682
	75	LT265/75 R 16	123/120 R	E	RWL	04506330000	Yes	31.6	52.4	80.0	10.5 (7.5)	(7.0 - 8.0)	3415	16	656
	75	LT285/75 R 16	126/123 R	E	RWL	04508480000	Yes	32.8	58.3	80.0	11.3 (8.0)	(7.5 - 9.0)	3750	16	633
	75	LT315/75 R 16	127/124 R	E	RWL	04508490000	Yes	34.6	64.6	65.0	12.3 (8.5)	(8.0 - 11.0)	3860	16	600
	85	LT235/85 R 16	120/116 S	E	RWL	04508440000	Yes	31.7	49.5	80.0	9.3 (6.5)	(6.0 - 7.5)	3085	16	655
17	12.50	35 X 12.50 R 17 LT	121 R	E	RWL	04507150000	Yes	35.0	62.9	65.0	12.5 (10.0)	(8.5 - 11.0)	3195	16	594
	65	265/65 R 17	112 T	SL	RWL	04509760000	Yes	30.6	43.2	44.0	10.7 (8.0)	(7.5 - 9.5)	2469	14	680
	70	245/70 R 17	110 T	SL	RWL	04509740000	Yes	30.5	40.5	44.0	9.8 (7.0)	(6.5 - 8.0)	2337	14	681
	70	LT245/70 R 17	119/116 R	E	RWL	04494490000	Yes	30.5	46.4	80.0	9.8 (7.0)	(6.5 - 8.0)	3000	17	681
	70	255/70 R 17	112 T	SL	RWL	04509750000	Yes	31.1	42.1	44.0	10.2 (7.5)	(6.5 - 8.5)	2469	14	669
	70	265/70 R 17	115 T	SL	RWL	04507630000	Yes	31.6	44.4	44.0	10.7 (8.0)	(7.0 - 9.0)	2679	14	657
	70	LT265/70 R 17	112/109 T	C	BSW	04509790000	Yes	31.6	46.9	50.0	10.7 (8.0)	(7.0 - 8.5)	2470	16	657
	70	LT265/70 R 17	121/118 S	E	RWL	04505740000	Yes	31.6	53.0	80.0	10.7 (8.0)	(7.0 - 8.5)	3195	16	657
	70	LT275/70 R 17	121/118 R	E	RWL	04508360000	Yes	32.2	56.7	80.0	11.0 (8.0)	(7.0 - 8.5)	3195	16	646
	70	LT285/70 R 17	121/118 S	E	RWL	04507250000	Yes	32.7	58.0	80.0	11.5 (8.5)	(7.5 - 9.0)	3195	16	635
	70	LT315/70 R 17	121/118 S	E	RWL	04508340000	Yes	34.4	65.7	65.0	12.7 (9.5)	(8.0 - 11.0)	3195	16	605
	75	LT245/75 R 17	121/118 S	E	RWL	04509880000	Yes	31.5	50.5	80.0	9.8 (7.0)	(6.5 - 7.5)	3195	16	660
	80	LT235/80 R 17	120/117 R	E	BSW	04508510000	Yes	31.8	49.5	80.0	9.3 (6.5)	(6.0 - 7.5)	3086	16	653
	12.50	35 X 12.50 R 18 LT	123 R	E	RWL	04505650000	Yes	35.0	65.6	65.0	12.5 (10.0)	(8.5 - 11.0)	3415	16	594
18	60	LT285/60 R 18	122/119 S	E	BSW	04508250000	Yes	31.5	54.7	80.0	11.5 (8.5)	(8.0 - 10.0)	3305	16	660
	65	275/65 R 18	116 T	SL	RWL	04509720000	Yes	32.1	45.2	44.0	11.0 (8.0)	(7.5 - 9.5)	2756	14	648
	65	LT275/65 R 18	123/120 R	E	RWL	04506340000	Yes	32.1	56.4	80.0	11.0 (8.0)	(7.5 - 9.0)	3415	16	648
	65	LT285/65 R 18	125/122 S	E	RWL	04508270000	Yes	32.6	57.0	80.0	11.5 (8.5)	(8.0 - 10.0)	3640	16	637
	70	255/70 R 18	113 T	SL	RWL	04492670000	Yes	32.1	43.3	44.0	10.2 (7.5)	(6.5 - 8.5)	2535	14	648
	70	265/70 R 18	116 T	SL	RWL	04504090000	Yes	32.6	45.8	44.0	10.7 (8.0)	(7.0 - 9.0)	2756	14	637
	70	LT265/70 R 18	124/121 S	E	RWL	04506020000	Yes	32.6	55.1	80.0	10.7 (8.0)	(7.0 - 9.0)	3525	16	637

BSW = Black Sidewall | RWL = Raised White Letter



GRABBER A/T^x | Product Data

LT/SUV | ALL-SEASON | ALL-TERRAIN

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
18	70	275/70 R 18	116 S	SL	BSW	04492430000	Yes	33.2	45.5	44.0	11.0 (8.0)	(7.0 - 9.0)	2756	14	627
	70	LT275/70 R 18	125/122 R	E	RWL	04506780000	Yes	33.2	59.2	80.0	11.0 (8.0)	(7.0 - 8.5)	3640	16	627
20	12.50	33 X 12.50 R 20 LT	114 S	E	BSW	04508130000	Yes	33.0	64.3	65.0	12.5 (10.0)	(8.5 - 11.0)	2600	16	630
	12.50	35 X 12.50 R 20 LT	121 R	E	BSW	04505690000	Yes	35.0	71.2	65.0	12.5 (10.0)	(8.5 - 11.0)	3195	16	594
	13.50	37 X 13.50 R 20 LT	127 R	E	BSW	15571240000	Yes	37.0	76.2	65.0	13.6 (11.0)	(8.5 - 11.0)	3860	16	561
	50	265/50 R 20	107 T	SL	BSW	04492690000	Yes	30.4	40.2	44.0	10.9 (8.5)	(7.5 - 9.5)	2149	14	683
	50	305/50 R 20	120 T	XL	BSW	04508150000	Yes	32.0	48.9	51.0	12.4 (9.5)	(8.5 - 11.0)	3086	14	649
	55	275/55 R 20	113 T	SL	BSW	04509770000	Yes	31.9	45.4	44.0	11.2 (8.5)	(7.5 - 9.5)	2535	14	651
	55	LT275/55 R 20	115/112 T	D	BSW	04508180000	Yes	31.9	55.1	65.0	11.2 (8.5)	(7.5 - 9.5)	2680	15	651
	55	LT285/55 R 20	117/114 T	D	BSW	04508170000	Yes	32.3	61.2	65.0	11.7 (9.0)	(8.0 - 10.0)	2833	15	642
	55	LT305/55 R 20	121/118 S	E	BSW	04508160000	Yes	33.2	59.7	65.0	12.4 (9.5)	(8.5 - 11.0)	3195	16	626
	60	LT265/60 R 20	121/118 S	E	BSW	04508220000	Yes	32.5	57.4	80.0	10.7 (8.0)	(7.5 - 9.5)	3195	16	639
	60	275/60 R 20	116 T	XL	BSW	04492700000	Yes	33.0	49.0	50.0	11.0 (8.0)	(7.5 - 9.5)	2756	14	630
	60	LT275/60 R 20	119/116 S	D	BSW	04508210000	Yes	33.0	56.4	65.0	11.0 (8.0)	(7.5 - 9.5)	2998	16	630
	60	LT285/60 R 20	125/122 S	E	BSW	04508200000	Yes	33.5	60.7	80.0	11.5 (8.5)	(8.0 - 10.0)	3640	16	621
	60	LT325/60 R 20	126 S	E	BSW	04508190000	Yes	35.4	70.8	65.0	13.0 (9.5)	(9.0 - 12.0)	3750	16	588
	65	LT275/65 R 20	126/123 S	E	BSW	04508230000	Yes	34.1	58.5	80.0	11.0 (8.0)	(7.5 - 9.5)	3750	16	610
22	12.50	33 X 12.50 R 22 LT	114 Q	F	BSW	04491700000	Yes	33.0	61.0	80.0	12.50 (10.0)	(8.5 - 11.0)	2600	17	944
	12.50	35 X 12.50 R 22 LT	121 Q	F	RWL	04491740000	Yes	35.0	69.5	80.0	12.5 (10.0)	(8.5 - 11.0)	3195	17	594
	12.50	37 X 12.50 R 22 LT	127 Q	F	RWL	04491750000	Yes	37.0	69.9	80.0	12.50 (10.0)	(8.5 - 11.0)	3860	17	561
	45	305/45 R 22	118 T	XL	BSW	04491710000	Yes	32.8	46.5	51.0	11.9 (10.0)	(9.5 - 11.5)	2910	14	633

BSW = Black Sidewall | RWL = Raised White Letter