

LT

LT / SUV / CUV



ON/OFF-ROAD ALL-TERRAIN

The Open Country A/T III all-terrain tire delivers gripping off-road traction with responsive and predictable on-road handling. With a strong focus on wet performance, durability, and treadwear life, and using Toyo's proprietary T-mode tire development and modeling technologies, Toyo introduces advanced tread design, construction, and compounding. The Open Country A/T III provides a quiet ride with exceptional stability, instilling driving confidence no matter the terrain. Built tough, it offers peace of mind to safely get there and back home, regardless of terrain or weather. With a treadwear warranty of up to 65,000 miles, outdoor adventurers can rely on the Open Country A/T III for the long haul.

MILEAGE WARRANTY*

P/Euro-Metric Sizes: 65,000-miles
LT Sizes: 50,000-miles

POPULAR FITMENTS

Chevrolet & GMC Trucks, SUVs and CUVs
Ford F-Series, CUVs and SUVs
Jeep
Ram Series
Toyota Trucks, SUVs and CUVs
Nissan Trucks, SUVs and CUVs
Subaru SUVs and CUVs

UTQG

P/Euro-Metric Sizes:
• S/T-Rated: 600 A B
• H-Rated: 600 A A



Three-Peak Mountain
Snowflake qualified for
severe snow conditions.

ADVANCED TREAD COMPOUND AND DESIGN

- Provides confident wet braking and handling.
- Provides cut-and-chip resistance.
- Provides excellent off-road grip.
- Delivers a quiet and comfortable ride.

OPEN COUNTRY A/T III

MORE EVENLY DISTRIBUTED VOID AREA

- Enhances on and off-road traction.
- Increases tread block rigidity for excellent handling stability.
- Provides better worn appearance.

STAGGERED SHOULDER LUGS

- Enhance off-road traction with biting edges.

INCREASED LATERAL GROOVES

- Enhance traction on all surfaces, including snow.

3D MULTI-WAVE SIPES

- Enhance wet and snow traction.
- Reduce irregular wear.

STONE-EJECTING BLOCKS

- Eject stones from grooves.



LT

LT / SUV / CUV

	WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)**	OVERALL WIDTH (IN.)**	MAX LOAD SINGLE (LBS)	MAX LOAD DUAL (LBS)	MAX PRESSURE (PSI)	REVS PER MILE
15		P215/75R15	100T	SL	OWL	356060	5.5-(6.0)-7.0	28	12.7	27.7	8.5	1742	-	44	751
		P225/75R15	102T	SL	BSW	356070	(6.0) -7.5	28	12.9	28.3	8.8	1874	-	44	734
		P235/75R15	108T	XL	OWL	356080	6.0-(6.5)-8.0	32	13.0	28.9	9.3	2183	-	50	720
		LT235/75R15	104/101S	C	OWL	355610	6.0-(6.5)-8.0	37	16.0	29.1	9.3	1985	1820	50	714
		P265/75R15	112S	SL	OWL	355280	7.0-(7.5)-9.0	38	13.4	30.7	10.5	2469	-	44	677
		30X9.50R15LT	104S	C	OWL	356050	6.0-(7.5)-8.0	40	15.6	29.8	9.4	1985	-	50	698
		31X10.50R15LT	109S	C	OWL	355910	7.0-(8.5)-9.0	43	15.6	30.7	10.6	2270	-	50	676
		215/65R16	102T	XL	BSW	356380	6.0-(6.5)-7.5	28	12.7	27.0	8.7	1874	-	50	769
		215/70R16	100T	SL	BSW	356090	5.5-(6.5)-7.0	29	12.7	27.9	8.7	1764	-	44	745
		LT215/85R16	115/112Q	E	BSW	355760	5.5-(6.0)-7.0	40	15.7	30.4	8.5	2680	2470	80	683
16		225/70R16	103T	SL	OWL	356100	6.0-(6.5)-7.5	30	12.9	28.4	9.0	1929	-	44	731
		P225/75R16	104S	SL	BSW	355260	(6.0) -7.5	30	12.9	29.3	8.8	1984	-	44	709
		LT225/75R16	115/112Q	E	BSW	355600	(6.0) -7.5	38	15.9	29.3	8.8	2680	2470	80	709
		235/70R16	106T	SL	BSW	356110	6.0-(7.0)-8.0	32	13.0	29.0	9.4	2094	-	44	717
		235/70R16	106T	SL	OWL	356120	6.0-(7.0)-8.0	32	13.0	29.0	9.4	2094	-	44	717
		LT235/85R16	120/116R	E	BSW	355770	6.0-(6.5)-7.5	44	16.0	31.7	9.3	3042	2778	80	655
		P245/70R16	106S	SL	OWL	355210	6.5-(7.0)-8.0	35	13.1	29.5	9.8	2094	-	44	704
		P245/70R16	106S	SL	BSW	355220	6.5-(7.0)-8.0	34	13.1	29.5	9.8	2094	-	44	704
		LT245/75R16	120/116S	E	BSW	355620	6.5-(7.0)-8.0	44	16.1	30.5	9.8	3042	2778	80	682
		LT245/75R16	120/116S	E	OWL	355630	6.5-(7.0)-8.0	44	16.1	30.7	9.8	3042	2778	80	676
		245/75R16	111T	SL	OWL	356140	6.5-(7.0)-8.0	35	13.1	30.5	9.8	2403	-	44	682
		245/75R16	111T	SL	BSW	356130	6.5-(7.0)-8.0	36	13.1	30.5	9.8	2403	-	44	682
		255/65R16	109T	SL	BSW	356150	7.0-(7.5)-9.0	33	13.2	29.1	10.2	2271	-	44	715
		255/70R16	115T	XL	BSW	356160	6.5-(7.5)-8.5	38	13.2	30.1	10.2	2679	-	50	691
		255/70R16	115T	XL	OWL	356170	6.5-(7.5)-8.5	37	13.2	30.1	10.2	2679	-	50	691
		P265/70R16	111T	SL	OWL	355230	7.0-(8.0)-9.0	39	13.4	30.6	10.7	2403	-	44	678
		P265/70R16	111T	SL	BSW	355240	7.0-(8.0)-9.0	40	13.4	30.6	10.7	2403	-	44	678
		LT265/75R16	123/120R	E	BSW	355650	7.0-(7.5)-9.0	50	16.3	31.7	10.5	3415	3085	80	656
		LT265/75R16	123/120R	E	OWL	355660	7.0-(7.5)-9.0	48	16.3	31.9	10.5	3415	3085	80	651
		265/75R16	116T	SL	BSW	356180	7.0-(7.5)-9.0	41	13.4	31.7	10.5	2756	-	44	656
		265/75R16	116T	SL	OWL	356190	7.0-(7.5)-9.0	41	13.4	31.7	10.5	2756	-	44	656
		LT285/75R16	126/123R	E	OWL	355670	7.5-(8.0)-9.5	56	16.5	33.1	11.3	3750	3415	80	628
		LT285/75R16	126/123R	E	BSW	355680	7.5-(8.0)-9.5	59	16.5	32.8	11.3	3750	3415	80	633
		LT295/75R16	128/125R	E	BSW	355720	7.5-(8.0)-10.0	62	16.6	33.4	11.6	3970	3640	80	622
		LT305/70R16	124/121R	E	BSW	355570	8.0-(9.0)-10.0	63	16.8	32.8	12.2	3525	3195	65	633
		LT315/75R16	127/124R	E	BSW	355730	8.0-(8.5)-10.5	66	16.9	34.6	12.3	3860	3525	65	601
17		215/65R17	103T	XL	BSW	355890	6.0-(6.5)-7.5	29	12.7	28.0	8.7	1929	-	44	741
		225/60R17	103T	XL	BSW	356390	6.0-(6.5)-8.0	30	12.9	27.6	9.0	1929	-	50	752
		LT225/65R17	107/103S	D	BSW	356910	(6.5) -8.0	38	15.9	28.5	9.0	2150	1930	65	729
		225/65R17	102T	SL	BSW	356400	6.0-(6.5)-8.0	30	12.9	28.5	9.0	1874	-	44	729
		235/65R17	108H	XL	BSW	356200	6.5-(7.0)-8.5	33	13.0	29.1	9.4	2205	-	50	715
		P235/75R17	108S	SL	BSW	355270	6.0-(6.5)-8.0	35	13.0	30.9	9.3	2205	-	44	673
		LT235/80R17	120/117R	E	BSW	355740	6.0-(6.5)-8.0	43	16.0	31.8	9.3	3085	2835	80	653
		LT245/65R17	111/108T	D	BSW	356520	(7.0) -8.5	41	16.1	29.5	9.8	2405	2205	65	704
		245/65R17	111T	XL	BSW	356210	(7.0) -8.5	34	13.1	29.5	9.8	2403	-	50	704
		245/65R17	111T	XL	OWL	356220	(7.0) -8.5	34	13.1	29.5	9.8	2403	-	50	704
		LT245/70R17	119/116R	E	BSW	355470	6.5-(7.0)-8.0	42	16.1	30.6	9.8	3000	2755	80	680
		245/70R17	110T	SL	BSW	356230	6.5-(7.0)-8.0	35	13.1	30.6	9.8	2337	-	44	680
		LT245/75R17	121/118S	E	BSW	355640	6.5-(7.0)-8.0	44	16.1	31.5	9.8	3195	2910	80	660
		LT255/65R17	114/110S	D	BSW	357160	(7.5) -9.0	45	16.3	30.1	10.2	2600	-	65	691
		LT255/70R17	121/118S	E	BSW	356920	6.5-(7.5)-8.5	47	16.3	31.1	10.2	3195	2910	80	668
		255/70R17	112T	SL	BSW	356240	6.5-(7.5)-8.5	38	13.2	31.1	10.2	2469	-	44	668
		LT255/75R17	111/108S	C	BSW	356930	6.5-(7.0)-8.5	48	16.3	32.0	10.0	2405	2205	50	648
		LT255/80R17	121/118R	E	BSW	355750	6.5-(7.0)-8.5	51	16.3	33.1	10.0	3195	2910	80	628
		LT265/65R17	120/117S	E	BSW	356610	(8.0) -9.5	49	16.3	30.6	10.7	3085	2835	80	680
		265/65R17	116T	XL	BSW	356250	7.5-(8.0)-9.5	38	13.4	30.6	10.7	2756	-	50	680
		LT265/70R17	121/118S	E	BSW	355480	7.0-(8.0)-9.0	48	16.3	31.7	10.7	3195	2910	80	656
		LT265/70R17	121/118S	E	OWL	355490	7.0-(8.0)-9.0	48	16.3	31.7	10.7	3195	2910	80	656
		LT265/70R17	112/109T	C	BSW	356940	7.0-(8.0)-9.0	50	16.3	31.7	10.7	2470	-	50	656
		265/70R17	115T	SL	BSW	356260	7.0-(8.0)-9.0	40	13.4	31.7	10.7	2679	-	44	656
		265/70R17	115T	SL	OWL	356270	7.0-(8.0)-9.0	42	13.4	31.7	10.7	2679	-	44	656
		LT275/70R17	124/121T	E	BSW	356550	7.0-(8.0)-9.0	51	16.4	32.2	11.0	3525	3195	80	645

	WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)**	OVERALL WIDTH (IN.)**	MAX LOAD SINGLE (LBS)	MAX LOAD DUAL (LBS)	MAX PRESSURE (PSI)	REVS PER MILE
17		P285/70R17	117T	SL	BSW	355250	7.5-(8.5)-9.5	46	13.6	32.8	11.5	2833	-	44	634
		LT285/70R17	116/113Q	C	BSW	355530	7.5-(8.5)-9.5	55	16.5	32.8	11.5	2755	2535	50	634
		LT285/70R17	121/118S	E	OWL	355540	7.5-(8.5)-9.5	53	16.5	33.0	11.5	3195	2910	80	630
		LT285/70R17	121/118S	E	BSW	355550	7.5-(8.5)-9.5	55	16.5	32.8	11.5	3195	2910	80	634
		LT285/75R17	121/118S	E	BSW	355700	7.5-(8.0)-9.5	60	16.5	33.9	11.3	3195	2910	80	614
		LT285/75R17	117/114Q	C	BSW	355690	7.5-(8.0)-9.5	59	16.5	33.9	11.3	2835	2600	50	614
		LT305/70R17	121/118R	E	BSW	355580	8.0-(9.0)-10.0	64	16.8	33.9	12.2	3195	2910	65	614
		LT315/70R17	121/118S	D	BSW	355590	8.0-(9.5)-10.5	67	16.9	34.4	12.7	3195	2910	50	604
		33X12.50R17LT	124S	F	BSW	356960	8.5-(10.0)-11.0	60	16.9	32.5	12.5	3525	-	80	639
		34X10.50R17LT	120S	D	BSW	356970	7.0-(8.5)-9.0	55	15.6	33.5	10.6	3085	-	65	620
18		35X11.50R17LT	118Q	C	BSW	355920	7.5-(9.0)-10.0	63	16.9	34.5	11.4	2910	-	50	602
		35X12.50R17LT	121R	E	BSW	355960	8.0-(10.0)-10.5	65	16.9	34.5	12.5	3195	-	65	602
		35X12.50R17LT	111Q	C	BSW	356540	8.0-(10.0)-10.5	59	16.9	34.5	12.5	2405	-	35	602
		37X12.50R17LT	128S	E	BSW	357010	8.0-(10.0)-10.5	73	16.9	36.5	12.5	3970	-	65	569
		37X13.50R17LT	128S	E	BSW	357150	9.0-(11.0)-11.5	79	16.9	36.5	13.6	3970	-	65	569
		225/55R18	102H	XL	BSW	355830	6.0-(7.0)-8.0	30	12.9	27.8	9.2	1874	-	50	748
		225/60R18	104T	XL	BSW	356410	6.0-(6.5)-8.0	32	12.9	28.6	9.0	1984	-	50	726

	WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)**	MAX LOAD SINGLE (LBS)	MAX LOAD DUAL (LBS)	MAX PRESSURE (PSI)	REVS PER MILE
20		275/55R20	117T	XL	BSW	355850	7.5-(8.5)-9.5	42	13.5	31.9	11.2	2833	-	50	651
		LT275/60R20	123/120T	E	BSW	356510	(8.0)-9.5	55	16.4	33.0	11.0	3415	3085	80	630
		275/60R20	115T	SL	BSW	356340	7.5-(8.0)-9.5	43	13.5	33.0	11.0	2679	-	44	630
		LT275/65R20	126/123S	E	BSW	355420	(8.0)-9.5	55	16.4	34.1	11.0	3750	3415	80	609
		P285/55R20	114T	SL	BSW	356440	8.0-(9.0)-10.0	45	13.6	32.4	11.7	2601	-	44	642
		P285/60R20	116T	SL	BSW	357170	8.0-(8.5)-10.0	48	13.6	33.5	11.5	2756	-	44	621
		LT285/55R20	122/119T	E	BSW	356350	8.5-(9.0)-10.0	54	16.5	32.4	11.7	3305	3000	80	642
		LT285/60R20	125/122R	E	BSW	355340	(8.5)-10.0	56	16.5	33.5	11.5	3640	3305	80	621
		LT285/65R20	127/124S	E	BSW	356470	(8.5)-10.0	56	16.5	34.6	11.5	3860	3525	80	601
		LT295/55R20	123/120T	E	BSW	356360	8.5-(9.5)-10.5	58	16.6	32.8	12.2	3415	3085	80	634
		P295/55R20	116T	SL	BSW	356630	8.0-(9.5)-10.5	49	13.7	32.8	12.2	2756	-	44	634
		LT295/60R20	126/123S	E	BSW	355350	(8.5)-10.5	60	16.6	33.9	11.8	3750	3415	80	612
		LT295/65R20	129/126S	E	BSW	355440	(8.5)-10.5	63	16.6	35.1	11.8	4080	3750	80	592
		305/50R20	120T	XL	BSW	355820	8.5-(9.5)-11.0	47	13.9	32.0	12.4	3086	-	50	648
		LT305/55R20	125/122Q	F	BSW	355320	9.0-(9.5)-11.0	65	16.8	33.2	12.4	3640	3305	80	625
		LT325/60R20	126/123R	E	BSW	355370	(9.5)-11.5	70	17.0	35.4	13.0	3750	3415	65	588
		33X12.50R20LT	119Q	F	BSW	355940	8.5-(10.0)-11.0	63	16.9	32.5	12.5	3000	-	80	639
		35X11.50R20LT	124R	E	BSW	356480	8.0-(9.0)-10.5	66	16.9	34.5	11.4	3525	-	80	602
		35X12.50R20LT	121R	E	BSW	355980	8.5-(10.0)-11.0	68	16.9	34.5	12.5	3195	-	65	602
		35X12.50R20LT	125Q	F	BSW	355990	8.5-(10.0)-11.0	67	16.9	34.5	12.5	3640	-	80	602
22		35X13.50R20LT	126Q	F	BSW	356040	9.5-(11.0)-12.0	71	16.9	34.5	13.6	3750	-	80	602
		37X12.50R20LT	126Q	E	BSW	356020	8.5-(10.0)-11.0	73	16.9	36.5	12.5	3750	-	65	569
		275/50R22	111T	SL	BSW	356900	7.5-(8.5)-9.5	47	13.5	32.9	11.2	2403	-	44	632
		285/45R22	114H	XL	BSW	355780	9.0-(9.5)-10.5	44	13.6	32.1	11.2	2601	-	50	647
		LT285/50R22	121/118R	E	BSW	355290	8.5-(9.0)-10.0	56	16.5	33.3	11.7	3195	2910	80	624
		LT285/55R22	124/121S	E	BSW	355310	8.5-(9.0)-10.0	63	16.5	34.4	11.7	3525	3195	80	604
		LT295/50R22	122/119T	E	BSW	356490	8.5-(9.5)-10.5	62	16.6	33.7	12.2	3305	3000	80	617
		LT295/55R22	125/122T	E	BSW	356460	8.0-(9.5)-10.5	63	16.6	34.8	12.2	3640	-	80	598
		305/45R22	118S	XL	BSW	356370	9.5-(10.0)-11.5	48	13.9	32.8	11.9	2910	-	50	633
		LT325/50R22	127Q	F	BSW	355300	9.5-(10.0)-11.5	72	17.0	34.8	13.2	3860	-	80	596
		33X12.50R22LT	109R	E	BSW	355950	8.5-(10.0)-11.0	59	16.9	32.5	12.5	2270	-	65	639
		35X12.50R22LT	121Q	F	BSW	356000	8.5-(10.0)-11.0	69	16.9	34.5	12.5	3195	-	80	602
		37X12.50R22LT	127Q	F	BSW	356030	8.5-(10.0)-11.0	75	16.9	36.5	12.5	3860	-	80	569



LT

LT / SUV / CUV

LT

LT / SUV / CUV



OPEN COUNTRY A/T III
P/EURO-METRIC

OPEN COUNTRY A/T III
LT-METRIC

OPEN COUNTRY A/T III
FLOTATION

OPEN COUNTRY A/T III
OWL AVAILABLE