

The GEOLANDAR X-CV is engineered to perform on today's luxury sport crossovers and SUVs.

FEATURES AND BENEFITS



SUPERIOR HANDLING

Innovative tread pattern with reinforced shoulder provides sharp, sure handling and stability.



ALL-SEASON GRIP

Specially designed tread pattern for confident traction on wet and wintry roads.



QUIET RIDE

A staggered five-pitch block variation reduces noise.



LONG TREAD LIFE

A wider flat contact patch and new advanced silica compound promotes long-lasting, even wear.

50,000-Mile Limited Treadwear Warranty (Non-Staggered Fitments and Front Position Staggered Fitments)

25,000-Mile Limited Treadwear Warranty (Rear Position Staggered Fitments)



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
235/60R18 107W	110157027	XL	520/A/A	31.8	7	6.5 - 8.5	9.6	29.1	7.3	11	13.3	714	2149@50	-	BW
255/55R18 109W	110157001	XL	520/A/A	32.6	8	7.0 - 9.0	10.5	28.9	8	11	13.2	720	2271@50	-	BW
225/45R19 96W	110157045	XL	520/A/A	26.7	7.5	7.0 - 8.5	8.8	27	7.4	11	12.6	770	1565@50	-	BW
235/45R19 99W	110157002	XL	520/A/A	25.8	8	7.5 - 9.0	9.3	27.3	7.6	11	12.7	760	1709@50	-	BW
235/55R19 105W	110157003	XL	520/A/A	30	7.5	6.5 - 8.5	9.5	29.1	7.3	11	13.5	713	2039@50	-	BW
235/60R19 103W	110157038	SL	520/A/A	31.4	7	6.5 - 8.5	9.6	30.1	7.3	11	13.8	691	1929@51	-	BW
255/45R19 104W	110157047	XL	520/A/A	31.3	8.5	8.0 - 9.5	10.1	28	8.3	11	13	742	1984@50	-	BW
255/50R19 107W	110157004	XL	520/A/A	32.4	8	7.0 - 9.0	10.4	28.9	8	11	13.4	718	2149@50	-	BW
255/55R19 111W	110157005	XL	520/A/A	35.1	8	7.0 - 9.0	10.5	29.9	8	11	13.8	694	2403@50	-	BW
265/50R19 110W	110157006	XL	520/A/A	34.8	8.5	7.5 - 9.5	10.7	29.3	8.3	11	13.5	708	2337@50	-	BW
265/55R19 109W	110157048	SL	520/A/A	36.1	8.5	7.5 - 9.5	10.9	30.4	8.4	11	14	683	2271@51	-	BW
275/50R19 112W	110157029	XL	520/A/A	37.1	8.5	7.5 - 9.5	11.1	29.8	8.7	11	13.7	696	2469@50	-	BW
275/55R19 111W	110157007	SL	520/A/A	39.5	8.5	7.5 - 9.5	11.3	30.7	8.6	11	14.1	676	2403@51	-	BW
235/45R20 100W	110157008	XL	520/A/A	27.6	8	7.5 - 9.0	9.2	28.3	7.6	11	13.3	733	1764@50	-	BW
235/50R20 104W	110157028	XL	520/A/A	29.6	7.5	6.5 - 8.5	9.5	29.3	7.4	11	13.6	709	1984@50	-	BW
245/45R20 103W	110157024	XL	520/A/A	28.9	8	7.5 - 9.0	9.6	28.7	8	11	13.4	725	1929@50	-	BW
255/40R20 101W	110157050	XL	520/A/A	30.5	9	8.5 - 10.0	10.1	28.1	8.5	11	13.2	738	1819@50	-	BW
255/45R20 105W	110157009	XL	520/A/A	31.1	8.5	8.0 - 9.5	10.2	28.9	8.3	11	13.5	719	2039@50	-	BW
255/50R20 109W	110157010	XL	520/A/A	34.8	8	7.0 - 9.0	10.5	29.9	8	11	13.9	694	2271@50	-	BW
255/55R20 110W	110157011	XL	520/A/A	35.1	8	7.0 - 9.0	10.4	30.8	8	11	14.2	674	2337@50	-	BW
265/45R20 108W	110157012	XL	520/A/A	32.8	9	8.5 - 10.0	10.6	29.2	8.6	11	13.6	711	2205@50	-	BW
265/50R20 111W	110157013	XL	520/A/A	35.1	8.5	7.5 - 9.5	10.8	30.3	8.3	11	14	685	2403@50	-	BW
275/40R20 106W	110157014	XL	520/A/A	33.1	9.5	9.0 - 11.0	11	28.6	9.1	11	13.3	727	2094@50	-	BW
275/45R20 110W	110157015	XL	520/A/A	35.3	9	8.5 - 10.5	11	29.6	8.9	11	13.7	702	2337@50	-	BW
275/50R20 113W	110157016	XL	520/A/A	39.2	8.5	7.5 - 9.5	11.2	30.7	8.7	11	14.2	677	2535@50	-	BW
285/45R20 112W	110157025	XL	520/A/A	39.5	9.5	9.0 - 10.5	11.3	30	9.3	12	13.9	693	2469@50	-	BW
295/40R20 110W	110157026	XL	520/A/A	39.3	10.5	10.0 - 11.5	11.9	29.1	9.8	12	13.5	714	2337@50	-	BW
235/45R21 101W	110157051	XL	520/A/A	29.5	8	7.5 - 9.0	9.4	29.3	7.6	11	13.7	708	1819@50	-	BW
235/50R21 101W	110157040	SL	520/A/A	31.5	7.5	6.5 - 8.5	9.5	30.4	7.4	11	14.2	683	1819@51	-	BW
245/45R21 104W	110157030	XL	520/A/A	29.8	8	7.5 - 9.0	9.6	29.7	8	11	13.9	700	1984@50	-	BW
245/50R19 105W	110157046	XL	520/A/A	31.5	7.5	7.0 - 8.5	10	28.7	7.8	11	13.3	724	2039@50	-	BW
255/40R21 102W	110157052	XL	520/A/A	31.4	9	8.5 - 10.0	10.1	29.2	8.5	11	13.7	712	1874@50	-	BW
265/40R21 105W	110157031	XL	520/A/A	32.2	9.5	9.0 - 10.5	10.6	29.4	8.7	11	13.8	705	2039@50	-	BW
265/45R21 104W	110157017	SL	520/A/A	32.2	9	8.5 - 10.0	10.7	30.2	8.6	11	14.1	688	1984@51	-	BW
275/40R21 107W	110157018	XL	520/A/A	33.5	9.5	9.0 - 11.0	11	29.6	9.1	11	13.9	702	2149@50	-	BW
275/45R21 110W	110157019	XL	520/A/A	35.9	9	8.5 - 10.5	10.9	30.6	8.9	11	14.3	678	2337@50	-	BW
285/40R21 109W	110157032	XL	520/A/A	36.1	10	9.5 - 11.0	11.3	30	9.4	12	14	692	2271@50	-	BW
285/45R21 113W	110157033	XL	520/A/A	38.7	9.5	9.0 - 10.5	11.3	31	9.3	12	14.4	670	2535@50	-	BW

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
295/35R21 107W	110157020	XL	520/A/A	34.2	10.5	10.0 - 11.5	11.6	29.1	9.8	12	13.6	715	2149@50	-	BW
295/40R21 111W	110157021	XL	520/A/A	37.3	10.5	10.0 - 11.5	11.9	30.2	9.8	12	14.1	688	2403@50	-	BW
315/35R21 111W	110157034	XL	520/A/A	39.2	11	10.5 - 12.5	12.6	29.6	10.4	12	13.9	701	2403@50	-	BW
315/40R21 115W	110157035	XL	520/A/A	41.9	11	10.5 - 12.5	12.6	30.8	10.4	12	14.3	674	2679@50	-	BW
255/45R22 107W	110157042	XL	520/A/A	33.8	8.5	8.0 - 9.5	10	31.1	8.3	11	14.6	667	2149@50	-	BW
265/35R22 102W	110157036	XL	520/A/A	30.6	9.5	9.0 - 10.5	10.6	29.4	8.8	11	13.9	707	1874@50	-	BW
265/40R22 106W	110157022	XL	520/A/A	34.6	9.5	9.0 - 10.5	10.6	30.3	8.7	11	14.2	685	2094@50	-	BW
275/40R22 108W	110157023	XL	520/A/A	35.7	9.5	9.0 - 11.0	10.9	30.6	9.1	11	14.4	679	2205@50	-	BW
HL275/45R22 115W	110157053	XL	520/A/A	37.8	9	8.5 - 10.5	10.8	31.7	8.9	11	14.8	655	2679@50	-	BW
285/35R22 106W	110157037	XL	520/A/A	34.5	10	9.5 - 11.0	11.3	30	9.4	11	14.1	693	2094@50	-	BW